LOC/DME I-AVP	APP CRS	Rwy Idg	7501
109.9	045°	TDZE	962
Chan 36		Apt Elev	962

ILS or LOC RWY 4

WILKES-BARRE/SCRANTON INTL (AVP)

Circling to Rwy 10, 28 NA at night. Circling NA for Cats C and D southeast of Rwy 4-22. Autopilot coupled approach NA below 2530. DME required. For inop ALS, increase S-ILS 4 all Cats visibility to RVR 5000, and S-LOC 4 Cat C/D visibility to 1⅝ SM.

MALSR

MISSED APPROACH: Climb to 3000 then climbing right turn to 4000 direct LVZ VORTAC and hold.

ATIS	WILKES-BARRE APP CON	WILKES-BARRE TOWER	GND CON
111.6	120.95 256.7 (280°-100°) 126.3 256.7 (101°-279°)	120.1 257.8	121.9



DME or RADAR required

ELEV 962 D TDZE 962



CATEGORY	A	B	C	D
S-ILS 4	1262/24 300 (300-1)			
S-LOC 4	1540/24 578 (600-1)		1540-1¼ 578 (600-1¼)	
C CIRCLING	1840-1¼ 878 (900-1¼)	1980-1½ 1018 (1100-1½)	1980-3 1018 (1100-3)	2280-3 1318 (1400-3)



HIRL Rwy 4-22
MIRL Rwy 10-28
REIL Rwys 10, 22, and 28

NE-4, 25 FEB 2021 to 25 MAR 2021
NE-4, 25 FEB 2021 to 25 MAR 2021