

WAAS CH 40315 W27A	APP CRS 274°	Rwy Idg 5502 TDZE 134 Apt Elev 141
--	------------------------	---


RNAV (GPS) RWY 27

DECATUR COUNTY INDUSTRIAL AIR PARK (BGE)

⚠ Baro-VNAV NA when using Tallahassee Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. VDP NA when using Tallahassee Intl altimeter setting. When local altimeter setting not received, use Tallahassee Intl altimeter setting and increase all DA 95 feet and all MDA 100 feet; increase LNAV/VNAV all Cats visibility ½ mile and LNAV Cat C visibility ¼ mile. For inoperative MALSR increase LNAV Cat D visibility to ¼ mile. For inoperative MALSR, when using Tallahassee Intl altimeter setting increase LPV all Cats visibility to 1 mile.

MALSR
 MISSED APPROACH:
Climb to 2500 direct FLSI and hold.



AWOS-3PT 121.125	TALLAHASSEE APP CON★ 128.7 254.3	UNICOM 122.975 (CTAF)
----------------------------	--	---------------------------------



SE-4, 25 FEB 2021 to 25 MAR 2021

SE-4, 25 FEB 2021 to 25 MAR 2021

ELEV 141	TDZE 134
----------	----------



CATEGORY	A	B	C	D
LPV DA	334-½ 200 (200-½)			
LNAV/VNAV DA	556-1 422 (500-1)			
LNAV MDA	540-½ 406 (400-½)	540-¾ 406 (400-¾)		540-1 406 (400-1)
CIRCLING	600-1 459 (500-1)	600-1½ 459 (500-1½)		700-2 559 (600-2)