



CHADM THREE DEPARTURE (RNAV)

SE-1, 25 FEB 2021 to 25 MAR 2021

DATIS 135.1
CLNC DEL 126.05
CPDLC
GND CON
121.9 348.6
NASHVILLE TOWER
118.6 257.8
NASHVILLE DEP CON
118.4 340.7

TAKEOFF MINIMUMS:
Rwys 2C, 2L, 2R, 13, 20C, 20L, 20R, 31: Standard
with minimum climb of 500' per NM to 1100.

TOP ALTITUDE:
4000



- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.
- NOTE: Radar required.
- NOTE: Transponder code will be issued via PDC or Nashville clearance delivery.
- NOTE: If unable to accept climb rates, advise ATC on initial contact.
- NOTE: For Turbojet aircraft only.

DEPARTURE ROUTE DESCRIPTION

- TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence...
- TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence...
- TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence...
- TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence...

...expect radar vectors to OZCAR, then on track 065° to CHADM. Maintain 4000, expect clearance to filed altitude within five (5) minutes after departure.

SWAPP TRANSITION (CHADM3.SWAPP):

NOTE: Chart not to scale.

SE-1, 25 FEB 2021 to 25 MAR 2021

CHADM THREE DEPARTURE (RNAV)