


EVWAN THREE DEPARTURE (RNAV)

TOP ALTITUDE:
4000

TAKEOFF MINIMUMS:

Rwys 2C, 2L, 2R, 13, 20C, 20L, 20R, 31: Standard with minimum climb of 500' per NM to 1100.


- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.
- NOTE: Radar required.
- NOTE: For Turbojet aircraft only.
- NOTE: Transponder code will be issued via PDC or Nashville clearance delivery.
- NOTE: If unable to accept climb rates, advise ATC on initial contact.



NOTE: Chart not to scale.

SE-1, 25 FEB 2021 to 25 MAR 2021

- D-ATIS 135.1
- CLNC DEL 126.05
- CPDLC
- GND CON
- 121.9 348.6
- NASHVILLE TOWER
- 118.6 257.8
- NASHVILLE DEP CON
- 118.4 360.7



DEPARTURE ROUTE DESCRIPTION

- TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence....
- TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence....
- TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence....
- TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence....
-expect radar vectors to CHPPY, then on track 115° to EVWAN. Maintain 4000, expect clearance to filed altitude within five (5) minutes after departure.

SE-1, 25 FEB 2021 to 25 MAR 2021

EVWAN THREE DEPARTURE (RNAV)