


PARDN THREE DEPARTURE (RNAV)


TOP ALTITUDE:
4000

D-ATIS 135.1
CLNC DEL 126.05
CPDIC
GND CON
121.9 348.6
NASHVILLE TOWER
118.6 257.8
NASHVILLE DEP CON
119.35 372.0



NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.
NOTE: Radar required.
NOTE: For Turbojet aircraft only.
NOTE: Transponder code will be issued via PDC or Nashville clearance delivery.
NOTE: If unable to accept climb rates, advise ATC on initial contact.

SE-1, 25 FEB 2021 to 25 MAR 2021



TAKEOFF MINIMUMS:

Rwys 2C, 2L, 2R, 13, 20L, 31: Standard with minimum climb of 500' per NM to 1100.
Rwys 20C, 20R: Standard with minimum climb of 500' per NM to 1300.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence...
TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence...
TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence...
TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence...

...expect radar vectors to KELLO, then on track 284° to PARDN. Maintain 4000. Expect clearance to filed altitude within five (5) minutes after departure.

HODJS TRANSITION (PARDN3.HODJS)
JJEFF TRANSITION (PARDN3.JJEFF)
NAKIY TRANSITION (PARDN3.NAKIY)

SE-1, 25 FEB 2021 to 25 MAR 2021