RNAV (GPS) RWY 19
NEW CASTLE (ILG)

WAAS CH 82115 W19A	APP CRS 195°	Rwy Idg 7012 TDZE 71 Apt Elev 80

Baro-VNAV NA when using Philadelphia Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Philadelphia Intl altimeter setting: increase LPV DA to 425, LNAV/VNAV DA to 592, and all MDA 60 feet; increase LPV all Cats and LNAV Cat D visibility ¼ mile.

MISSED APPROACH: Climb to 2000 direct FESER and hold.

ATIS	PHILADELPHIA APP CON	WILMINGTON TOWER*	GND CON	CLNC DEL	UNICOM
123.95	118.35 323.1	126.0 L (CTAF) 352.05	121.7 275.8	119.95	122.95







CATEGORY	A	B	C	D
LPV DA	371-1 300 (300-1)			
LNAV/VNAV DA	538-1¾ 467 (500-1¾)			
LNAV MDA	480-1 409 (400-1)		480-1¼ 409 (400-1¼)	
CIRCLING	540-1 460 (500-1)		600-1½ 520 (600-1½)	640-2 560 (600-2)

REIL Rwys 9, 19 and 27 L
HIRL Rwys 1-19 and 9-27 L
MIRL Rwy 14-32 L

NE-3, 25 FEB 2021 to 25 MAR 2021
NE-3, 25 FEB 2021 to 25 MAR 2021