VORTAC SBY	APP CRS	Rwy Idg	8005
111.2	SBY 24.1 Arc	TDZE	38
Chan 49		Apt Elev	40

VOR/DME or TACAN RWY 10

WALLOPS FLIGHT FACILITY (WAL)

When local altimeter setting not received, use Salisbury altimeter setting and increase all MDA 60 feet and Circling Cats C/D visibility ¼ mile. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climbing left turn to 2000 on heading 240° and SBY VORTAC 24.1 DME Arc clockwise to MAGGO/SBY 24.1 DME and hold.

ASOS	PATUXENT APP CON ★	WALLOPS TOWER ★	GND CON	CLNC DEL
119.175	127.95 314.0	126.5 (CTAF) L 306.975 (CTAF) L	127.875 269.325	121.7



CATEGORY	A	B	C	D
S-10	900-1¼	862 (900-1¼)	900-2½	862 (900-2½)
C CIRCLING	900-1¼	860 (900-1¼)	900-2½ 860 (900-2½)	900-2¾ 860 (900-2¾)

REIL all Rwys
HIRL Rwys 4-22, 10-28 and 17-35

NE-3, 25 FEB 2021 to 25 MAR 2021
NE-3, 25 FEB 2021 to 25 MAR 2021