

RADAR INSTRUMENT APPROACH MINIMUMS

ABILENE, TX

Amdt 10, 05JAN17 (17005) (FAA)

ELEV **1791**

ABILENE RGNL (ABI)

RADAR-1 125.0 338.3 (EAST), 127.2 282.3 (WEST) **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	17R		AB	2240-1	469	(500-1)	CDE	2240-1³/₈	469	(500-1 ³ / ₈)
	35R		AB	2340-1¹/₂	564	(600-1 ¹ / ₂)	CDE	2340-1¹/₄	564	(600-1 ¹ / ₄)
	35L		AB	2340-1	553	(600-1)	CDE	2340-1¹/₈	553	(600-1 ¹ / ₈)
C CIRCLING	ALL RWY		AB	2340-1	549	(600-1)	C	2420-1¹/₄	629	(700-1 ¹ / ₂)
			D	2460-2	669	(700-2)	E	2620-3	829	(900-2)

When control tower closed, ASR NA.

For inoperative ALS, increase ASR-35R CAT E visibility to 1% SM.

AMARILLO, TX

Amdt 16A, 31DEC20 (20366) (FAA)

ELEV **3607**

RICK HUSBAND AMARILLO INTL (AMA)

RADAR-1 119.5 307.0 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	22		ABC	3960-3¹/₄	367	(400-3 ¹ / ₄)	DE	3960-1¹/₄	367	(400-1 ¹ / ₄)
	31		ABCD	3960-1	362	(400-1)	E	NA		
	13		AB	4040-1	437	(500-1)	CD	4040-1¹/₄	437	(500-1 ¹ / ₄)
			E	NA						
	4		AB	4160/24	555	(600-1 ¹ / ₂)	C	4160/50	555	(600-1)
			D	4160/60	555	(600-1 ¹ / ₄)	E	4160-1¹/₂	555	(600-1 ¹ / ₂)
CIRCLING	ALL RWY		AB	4160-1	555	(600-1)	C	4160-1¹/₂	555	(600-1 ¹ / ₂)
			D	4260-2	635	(700-2)	E	4460-3	855	(900-3)

When control tower closed, procedure NA.

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021


RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

DYESS AFB (KDYS), TX (Abilene) (Amdt 3, 15344 USAF)

ELEV 1790

RADAR - (E) 121.3 127.2 270.3 282.3

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	34 ¹		AB CDE	2260/24 2260/50	472 472	(500-½) (500-1)
	16 ¹		AB CDE	2300/24 2300/55	510 510	(600-½) (600-1)
 CIR	16 ²		A B C D E	2300-1 2320-1¼ 2460-1¾ 2460-2 2460-2¼	510 530 670 670 670	(600-1) (600-1¼) (700-1¾) (700-2) (700-2¼)
	34 ³		A B C D E	2300-1 2320-1 2460-1¾ 2460-2 2460-2¼	510 530 670 670 670	(600-1) (600-1) (700-1¾) (700-2) (700-2¼)

¹When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1½ miles.

²Circling to other than Rwy 34 NA.

³Circling to other than Rwy 16 NA.

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

FORT WORTH NAS JRB (CARSWELL FLD) (NFW), Fort Worth, TX

18JUN20 (20170) (USN)

ELEV 650

RADAR - (E)¹ 128.775 371.875 ▼

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/</u>	<u>CEIL-VIS</u>
PAR ²	36 ⁴	3.0 ⁷ /59/1226	ABCDE	850-½	200	(200-½)
	18 ^{3,7}	3.0 ⁷ /61/1071	ABCDE	836-¾	200	(200-¾)
PAR W/O GS ²	18		AB	1040-1	404	(400-1)
			CDE	1040-1½	404	(400-1½)
			AB	1160-½	510	(600-½)
			CDE	1160-1	510	(600-1)
ASR ²	18 ⁹		AB	1120-1¼	484	(500-1¼)
			CDE	1120-1¾	484	(500-1¾)
			AB	1220-¾	570	(600-¾)
			CDE	1220-1¼	570	(600-1¼)
CIR	18-36 ⁸		A	1240-1¼	590	(600-1¼)
			B	1280-1¼	630	(700-1¼)
			C	1320-1¼	670	(700-1¼)
			D	1320-2	670	(700-2)
			E	1320-2¼	790	(800-2¼)

¹Opr 1300-0500Z++ Mon-Fri; clsd Sat, Sun and hol. Afld hr subject to chg by NOTAM. Base OPS/ATC not manned outside of publ hrs.

²No-NOTAM MP: PAR 1230-1530Z++ Tue, Thu; ASR 1230-1530Z++ Mon, Wed.

³CAUTION: PAR TCH exceeds 60'.

⁴When ALS inop, increase vis to ¾ mile.

⁵When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.

⁶When ALS inop, increase CAT AB vis to 1¼ miles, CAT CDE vis to 1¾ miles.

⁷CAUTION: WCH for Height Group 1 (53 ft) is higher than the maximum 50 ft. WCH Group 1 includes general aviation, small commuters, corporate turbojets, T-38, C-12, C-20, C-21, T-1, fighter jets, UC-35, T-3, T-6 aircraft.

⁸Circling not authorized E of Rwy 18-36.

⁹Step Down Fix at 2 NM from thld, 1320 min.

¹⁰Step Down Fix at 2 NM from RPI, 1300 min.

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

SHEPPARD AFB/WICHITA FALLS MUNI (KSPS), TX (17341 USAF)

ELEV 1019

RADAR^{1 2} - (E) Ctc SHEPPARD APP CON 118.2 269.025

⚠ NA when Sheppard Approach Control closed.

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATh/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR ³	15C ⁴		ABCDE	1420-¾	417	(500-¾)
	15R ⁴		ABCDE	1420-¾	422	(500-¾)
	33L ⁴		ABCDE	1440-¾	440	(500-¾)
	33C ⁵		AB	1440-¾	451	(500-¾)
			CDE	1440-¾	451	(500-¾)
CIR ⁶	ALL RWY		A	1440-1¼	421	(500-1¼)
			B	1480-1¼	461	(500-1¼)
			C	1480-1½	461	(500-1½)
			D	2020-3	1001	(1100-3)
			E	2080-3	1061	(1100-3)

¹Sheppard APP CON clsd 0200-1200Z++ Mon-Fri, 2300-1800Z++ Sun, clsd Sat and hol, ctc FORT WORTH CENTER 133.5 350.35.

²MP ASR 0600-1200Z++ Mon-Fri.

³ASR not avbl when Sheppard APP CON is clsd.

⁴When ALS inop, increase CAT ABCDE vis to 1¼ miles.

⁵When ALS inop, increase CAT AB vis to 1¼ miles, CAT CDE vis to 1½ miles.

⁶Circling not authorized West of Rwy 15R-33L.

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

RADAR INSTRUMENT APPROACH MINIMUMS