

RADAR MINS

19339

RADAR INSTRUMENT APPROACH MINIMUMS

CAMPBELL AAF (KHOP), (FORT CAMPBELL), KY (RADAR 1 Amdt 1A, RADAR 2 Amdt 2,

18144 USA)

RADAR - (E) 134.350x 237.5x 395.9x 258.3x 290.9x **T**

ELEV 571

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
RADAR-1						
ASR	5 ^{1 4 6 8} 23 ^{5 7 12}		ABCDE	920-1	365	(400-1)
			AB	980/24	409	(500-½)
			CDE	980/40	409	(500-¾)
CIR ⁹	5-23		AB	1060-1	489	(500-1)
			C	1060-1½	489	(500-1½)
			DE	1140-2	569	(600-2)
RADAR-2						
PAR ¹⁰	23 ^{2 3 5} 5 ^{1 3 4 11}	3.0°/55/1143 3.0°/50/941	ABCDE	771/24	200	(200-½)
			ABCDE	748-¾	200	(200-¾)

¹Procedure NA when R-3701, R-3702A/B in use.

²FAF 4.9 miles from threshold.

³Glideslope intercept altitude 2200.

⁴Final approach course 045.

⁵Final approach course 225.

⁶Recommended altitude 4 miles: 1880, 3 miles: 1560, 2 miles: 1240.

⁷Recommended altitude 4 miles: 1880, 3 miles: 1560, 2 miles: 1240.

⁸FAF 5.0 miles from threshold, min alt 2200.

⁹Circling NA SE of Rwy 5-23.

¹⁰PAR unavabl Sat-Sun 2300-0700Z++.

¹¹FAF 5.0 NM from thld.

¹²FAF 4.9 NM from thld, min alt 2200.

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

KNOXVILLE, TN

Amdt 22A, 08NOV18 (18312) (FAA)

ELEV 981

MC GHEE TYSON (TYS)

RADAR-1 123.9 360.8 **T A**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	5L		AB	1420/24	467	(500-½)	C	1420/40	467	(500-¾)
			D	1420/50	467	(500-1)	E	1420/60	467	(500-1¼)
	5R		AB	1420-1	461	(500-1)	C	1420-1¼	461	(500-1¼)
			D	1420-1½	461	(500-1½)	E	1420-1¾	461	(500-1¾)
	23R		AB	1520/40	539	(600-¾)	C	1520/50	539	(600-1)
			D	1520/60	539	(600-1¼)	E	1520-1½	539	(600-1½)
	23L		AB	1520-1¼	555	(600-1¼)	C	1520-1½	555	(600-1½)
			D	1520-1¾	555	(600-1¾)	E	1520-2	555	(600-2)
C CIRCLING ALL RWY			A	1520-1¼	539	(600-1¼)	B	1620-1¼	639	(700-1¼)
			C	1660-1½	679	(700-1½)	D	1900-2	919	(1000-2)
			E	1900-3	919	(1000-3)				

For inoperative ALSF-2 Rwy 23R and MALSR Rwy 5L increase CAT E visibility ½ mile.

SE-1

RADAR INSTRUMENT APPROACH MINIMUMS


RADAR MINS

19339

RADAR INSTRUMENT APPROACH MINIMUMS

SABRE AAF (KEOD), TN (Fort Campbell), (Amdt 3A, 18032 USA)

ELEV 595

RADAR - (E) 118.1 340.9  NA

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	23		COPTER	1060-½	473	(500-½)
	5		COPTER	1100-½	507	(600-½)

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

RADAR INSTRUMENT APPROACH MINIMUMS